


Rinnai



PB Series

Inverter Split System




Rinnai PB Series


Designed for Australia's ever-changing climate, the Rinnai PB Series Inverter Split System provides both optimal heating and cooling all year round no matter where you live.

Packed with innovative features including Wi-Fi connectivity, self-cleaning function and sleep mode, the PB Series is the ultimate in providing complete comfort. This smart system can also work around your unique lifestyle with an ultra-practical timer function, allowing you to set the unit's operation times to achieve the perfect room temperature.


Encased in a sleek contemporary design, the Rinnai PB Series range is durable, convenient and easy to maintain.



Innovation and Design



Rinnai GoldGuard



Competitors



GoldGuard

The Rinnai PB Series Condenser Coil is coated with our special GoldGuard coating making it more resistant to oxidation and corrosion than ordinary Condenser Coils. The GoldGuard condenser coil also improves the heating efficiency of the P Series in Reverse Cycle operation by accelerating the defrosting process.

Rinnai's unique GoldGuard coating uses nano technology to effectively prevent bacteria growth and deliver greater longevity and sustained performance of the outdoor unit in coastal areas and other harsh environments. Also, the coating is non-toxic and 100% environmentally friendly.



At Rinnai, we're all about comfort

For over 50 years, Rinnai has supplied Australian homes with a range of appliances that help people lead comfortable, safe and efficient lifestyles.

Being driven to create comfort means that we really care about our products and your experience from start to finish. We're focused on developing products with the latest technology and our level of quality is second-to-none, so you can rest assured knowing Rinnai will deliver.



Comfort at the touch of a button

Wi-Fi Control

The Rinnai PB Series features Wi-Fi control via an App.

Simple to activate and easy to use, the **NetHome Plus** App can be downloaded via Google Play or the App Store on a compatible mobile device.

Once installed and registered, you can operate your appliance on the go.

A host of functions like on/off, temperature control and fan speed can be accessed through the App. Best of all, the Wi-Fi control allows you to switch on your Air Conditioner from outside the home – creating the ultimate in convenience and comfort.

We're at your service

The National Customer Care Centre provides first class service and maintenance of your system, ensuring it's running at its highest efficiency - so you can enjoy the Rinnai experience for many years to come.

Operating 5 days a week
(Monday to Friday)

13 43 73



Turn your Air Conditioner on or off, set your temperature, fan speed and more remotely from anywhere in the world with an Internet connection.



Your home's Internet router relays requests from the App to control your Air Conditioner just like the normal remote controller.



Set your favourite temperature before you come home - enjoy the comfort and energy savings.



Available to download via:

- Google Play
- App Store



Features and Benefits



Wi-Fi Control

Set your favourite temperature from anywhere, with our intuitive Android or Apple App. Come home to ultimate comfort.



Superior Corrosion Protection

The Rinnai PB Series Condenser Coil is coated with our GoldGuard coating making it more resistant to oxidation and corrosion than ordinary Condenser Coils.



Inverter Technology

Powerful to heat and cool fast, but also smart, seamless operation to maintain consistent temperature and reduce running costs.



Quiet Operation

Designed to keep noise levels to a minimum without affecting performance, thanks to its clever design optimised to deliver better air distribution.



3D Airflow

Air blades can be controlled to swing both horizontally and vertically, allowing for balanced room temperature and comfort.



Turbo Function

Quickly cool in summer or swiftly warm in winter.



Dehumidifying Mode

Efficiently manages room humidity levels to ensure optimum comfort levels during humid summer days.



Timer

A delay ON or OFF timer allows you to select a period of time (from 30 minutes to 24 hours), the unit will turn either on or off depending on its current status.



Sleep Mode

The PB Series intelligent sleep mode operates on a two-way temperature control that modulates up and down to mimic outside ambient temperatures, ensuring a comfortable sleep.



Demand Control

Equipped with demand response capability (DRED) to help reduce overall power consumption at critical peak load times.**




R32 Refrigerant

R32 refrigerant has lower global warming potential than traditional refrigerants. Also provides higher energy efficiency while using lower refrigerant volumes.

*For full terms & conditions visit www.rinnai.com.au

**Subject to availability from your energy provider.

Zoned Energy Rating Label



1

Cooling Capacity

The amount of cooling the Air Conditioner can provide when the outside temperature is above 35°C.

2

Heating Capacity

The amount of heating the Air Conditioner can provide when the outside temperature is 7°C and below 2°C.

3

Model Name and Number

4

Noise Levels - Sound Power

How loud the Air Conditioner will be when it is running. The number inside the house shows the inside noise levels, the number outside of the house illustrates the noise levels near the outdoor unit.

5

Efficiency Ratings Based on Locations

The efficiency of a product will change, dependent on the location in which it operates. There are three bands of ratings - Hot, Average and Cold areas in Australia and New Zealand. Use the map to determine which band to use.

6

Electricity usage

How much electricity the Air Conditioner will use each year for heating and cooling.

How to read the label

The performance of air conditioners is affected by the climate it is operating in. For this reason, new non-ducted household air conditioners must display a new Zoned Energy Rating Label that considers the climate you live in. The label provides an energy rating for three climate zones (hot, average and cold), helping you select an appliance that performs best in your location. Estimated annual energy use in kilowatt hours (kWh) is provided on the right of the label, for heating (red) and cooling (blue) in each climate zone. In addition, it has output capacity for heating at two outdoor temperatures and cooling at one outdoor temperature, as well as noise indicators at the bottom to show the volume in decibels (dB(A)) of the air conditioner.

Technical Information

RINNAI - PB Series Hi-Wall Split System		HSNRP26B	HSNRP35B	HSNRP50B	HSNRP60B	HSNRP70B	HSNRP80B
Nominal Capacity	kW	2.65	3.55	5.00	6.00	7.15	8.00
Power Supply to Outdoor Unit	V - Ph - Hz	220-240 - 1 - 50					
Recommended Circuit Breaker	A	16	16	20	20	25	25
Connectivity		Wi-Fi Enabled					
Demand Response Enabling Device		DRED Enabled					
Cooling	Rated Capacity	kW	2.65	3.5	5.0	6.0	7.8
	Capacity Range		1.00-3.50	1.50-4.90	2.10-7.20	2.10-7.20	3.20-8.0
	Rated Power Input	W	530	790	1280	1750	1920
	Rated Current (Range)	A	2.5	3.8	5.8	8.0	10.5
	AEER	W/W	4.98	4.42	3.90	3.42	3.53
	TCSPF (Hot / Mixed / Cold)		8.02/7.497/7.887	7.00/6.76/7.07	6.19/5.83/6.17	5.86/5.61/5.99	5.36/5.14/5.37
	Star Rating (Hot / Average / Cold)	-	6.5 / 5.5 / 6.0 STAR	5.0 / 5.0 / 5.5 STAR	4.5 / 4.0 / 4.5 STAR	4.0 / 4.0 / 4.0 STAR	3.5/3.5/3.5
Heating	Rated Capacity	kW	2.7	3.8	5.4	6.5	8.3
	Capacity Range		1.40-4.00	1.80-5.10	2.50-7.80	2.50-7.80	2.20-8.8
	Rated Power Input	W	510	830	1340	1686	1990
	Rated Current (Range)	A	2.50	5.00	6.00	8.2	10.8
	ACOP	W/W	5.273	4.564	4.019	3.847	3.734
	HSPF (Hot / Mixed / Cold)		5.79/5.35/4.96	6.23/5.22/4.50	4.89/4.31/3.71	5.31/4.29/3.52	4.97/4.32/3.82
	Star Rating (Hot / Average / Cold)	-	4.0 / 3.5 / 3.0 STAR	4.5 / 3.5 / 3 STAR	3.0 / 2.5 / 2.0 STAR	3.5 / 2.5 / 2.0 STAR	3.0/2.5/2.0
Maximum Input Power (Cooling / Heating)		W	2300	2300	3600	3600	4050
Maximum Input Current (Cooling / Heating)		A	10.5	10.5	15.5	15.5	17.5
Suitable Area Coverage (up to 2.6m insulated ceiling)		m²	11-17	16-23	23-33	27-40	32-47
Indoor Unit Model No.		HINRP26MB	HINRP35MB	HINRP50MB	HINRP60MB	HINRP70MB	HINRP80B
Air Flow (Turbo / Hi / Med / Lo / Min)		L/s	175/139/100/83/56	183/147/106/86/58	264/222/167/139/89	264/222/167/139/89	382/303/250/229/147
Moisture Removal		L/h	1.00	1.20	1.80	2.10	3.00
Sound Pressure Level @ 1m (Turbo / Hi / Med / Lo / Min)		dB(A)	46.4/39/32.5/30/24.5	46.7/39/32.5/30/24.5	47.1/44.5/38/34.5/28	47.1/44.5/38/34.5/28	57.645/45/39/33.5/29.5
Air Swing Louvres		Direction	4-way swing				
Dimensions	Dimension (W x H x D)	mm	802x295x200	802x295x200	971x321x228	1082x337x234	1082x337x234
	Packing (W x H x D)		875x375x288	875x375x288	1045x405x308	1155x415x318	1155x415x318
	Net / Gross Weight	kg	8.5/11.5	8.5/11.5	111/15.2	111/15.2	13.5/17.8
Operating Range	Cooling	°C	16 - 32				
	Heating		0 - 30				
Outdoor Unit Model No.		HONRP26B	HONRP35B	HONRP50B	HONRP60B	HONRP70B	HONRP80B
Sound Power Level		dB(A)	57.8	58.5	65.2	65.2	65
Sound Pressure Level @ 1m			55.5	55.5	59.5	59.5	61
Dimensions	Dimension (W x H x D)	mm	805x554x330	805x554x330	890x673x342	890x673x342	890x673x342
	Packing (W x H x D)		915x615x370	915x615x370	995x740x398	995x740x398	995x740x398
	Net / Gross Weight	kg	32.2/35.1	32.2/35.1	38.3/41.6	38.3/41.6	42.4/46.9
Refrigerant	Type		R32				
	Charged Volume	kg	0.9	0.9	1.26	1.26	1.4
	Pipe Size: Liquid / Gas	mm	6.35/9.52	6.35/9.52	6.35/12.7	6.35/12.7	6.35/15.9
	Maximum Pipe Length	m	25	25	30	30	50
	Chargeless Length		10	10	10	10	10
	Extra Charge for Lengths >10m	g/m	12	12	12	12	12
	Maximum Vertical Separation	m	10	10	20	20	25
Ambient Temperature Limits	Cooling	°C	0 - 52	0 - 52	0 - 50	0 - 50	-15 - 50
	Heating		-15 - 24	-15 - 24	-15 - 24	-15 - 24	-15 - 24

Capacities tested in accordance with AS/NZS 3823.2, with 5m interconnecting pipe length. With our policy of continuous improvement, we reserve the right to change, or discontinue at any time, specifications or designs without notice.

Note: All images contained within this brochure are for illustrative purposes only, the colours and finishes of the products featured are as close to the respective product range as photographic lighting and printing processes allow.

Rinnai Australia Pty Ltd

ABN 74 005 138 769

100 Atlantic Drive,
Keysborough, Victoria 3173

For further information
call 1300 555 545 or visit
rinnai.com.au

TOTAL HOME COMFORT



HOT WATER



HEATING



COOLING

Rinnai